



Fiber Type: E-Glass
 Architecture: 0°/90° Biaxial
 Dry Thickness: 0.055 in. / 1.40 mm
 Total Weight: 27.24 oz/sq.yd / 924 g/sq.m

Roll Specifications			Fiber Architecture Data
Roll Width: 60 in. / 1524 mm	Roll Weight: 180 lbs / 136 kg	Roll Length: 62 yd / 57 m	0 ° : 12.22 oz/sq.yd / 414 g/sq.m
			45 ° : n/a
			90 ° : 11.52 oz/sq.yd / 391 g/sq.m
			- 45 ° : n/a
			Polyester Veil: 3.50 oz/sq.yd / 119 g/sq.m

* Packaging: Box or Bag

**Total weight refers to reinforcement material only (does not include stitching weight).

Disclaimer:

The customer is solely responsible for determining the performance and fitness for a particular use of any product produced by customer utilizing a reinforcement fabric or material produced or manufactured by Vectorply Corp. Specifications of reinforcements may change without notice.

REV: 8/13/2018



Distributed by

PrimeLine Products, Inc.
 "Your Prime Source for Solutions, Products, and Training"
 311 Altamonte Commerce Blvd #1608
 Altamonte Springs, FL 32714
 Office: 407-772-8131 Fax: 407-786-8131

Email: Sales@PrimeLineProducts.com Web: www.PrimeLineProducts.com