

PICOTE MAXI MILLER

A Proven Machine for Tough Jobs



The Maxi Miller is a high speed, high torque powerhouse designed for cleaning, descaling, and root removal in pipes ranging from DN70-250 (3-10") and cutting/reinstatements in DN70-200 (3-8") pipes.

When combined with the Maxi Coating Pump it has the capability of installing Picote Brush Coating™ in DN70-300 (3-12") pipes.

It has a reach of 30m (100') of 12mm (½") shaft which can be extended 10m (33') using a shaft extension.

USES AND BENEFITS

- The Maxi Miller opens the door for new jobs such as blockage and root removal, light and heavy descaling, reinstating lines in CIPP, epoxy coating, liner & concrete removal, and more.
- Optional Maxi Miller Plus model has a removable control unit on a 5m (16') cord.
- High Speed/High Torque: 500-1475 rpm.
- Standard safety features include: protective outer shaft casing, operator presence foot control, manual safety clutch, internal GFI, and an emergency stop to help keep you and your equipment investment protected.

Maxi Miller Technical Specifications

Pipe Size Ranges	
Cleaning / Descaling	DN70-250 (3-10")
Cutting / Reinstatement	DN70-200 (3-8")
Picote Brush Coating™	DN70-300 (3-12")
Usable Shaft Length	30m (100')
Shaft Extensions	10m (33')
Shaft Size	12mm (½")
Casing Type	Thick
Output Power	1.13kW
Speed	500-1475 RPM
Power	UK/US: 110/120V, 30 Amp EU: 220/230V, 16 Amp
Weight	89kg (196 lbs)
Size	1150 x 854 x 489mm 45 x 34 x 19"
Safety Features	Protective outer shaft casing, operator presence foot control, internal GFI, electric safety clutch, & emergency stop.
IP Class	54



More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on products, spare parts, assembly and operation, consult the Maxi Miller Operating Manual or contact Picote Technical Support.
- For hands-on product training, Picote operates training centers in USA, UK, and Finland.

PRODUCTS AND SPARE PARTS

Picote Maxi Miller Products and Parts	
PN	Description
3560032012US	Maxi Miller 110v - US
3560032012	Maxi Miller - 220v
3560042012US	Maxi Miller Plus, 110v - control box, 5m (16') cord - US
3560042012	Maxi Miller Plus, 220v - control box, 5m (16') cord
Spare Parts	
1312021125033	Maxi Miller 12mm (1/2") Shaft Thick Casing 33m (108')
9331012000	Thick Outer Shaft Casing for 12mm (1/2") shaft
1350000020	Picote Flexible Shaft Lubricant bottle (0.5 litres/17oz)
1350000021	Picote Flexible Shaft Lubricant package (6 bottles)



SALES - SERVICE - TRAINING

311 Altamonte Commerce Blvd #1608 Altamonte Springs, FL 32714
 Office: 407-772-8131 Fax: 407-786-8131
 Web: www.PrimeLineProducts.com Email: Sales@PrimeLineProducts.com